

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name

**Blair Scrub Free Alkaline Tire & Wheel**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Tire and engine degreaser

Uses advised against

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

#### 1.3 Details of the supplier of the safety data sheet

Blair Enterprises LLC  
18540 Apache Drive  
Parker, CO 80138  
1-720-383-4558

<https://blairceramics.com>  
[orders@blairceramics.com](mailto:orders@blairceramics.com)

#### 1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500  
24 hour emergency number

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	1B	Skin Corr. 1B	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
B.16	substance or mixture corrosive to metals	1	Met. Corr. 1	H290

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05



- Hazard statements

H290

May be corrosive to metals.

H314

Causes severe skin burns and eye damage.

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### - Precautionary statements

P234	Keep only in original container.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling potassium hydroxide

### 2.3 Other hazards

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
2-butoxy-1-ethanol	CAS No 111-76-2	3 - < 12	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 4 / H227
potassium hydroxide	CAS No 1310-58-3	3 - < 12	Acute Tox. 4 / H302 Skin Corr. 1A / H314 Met. Corr. 1 / H290
sodium dodecylbenzenesulfonate	CAS No 25155-30-0	1 - < 3	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2A / H319
sodium xylene sulphonate	CAS No 1300-72-7	1 - < 3	Skin Irrit. 2 / H315 Eye Irrit. 2B / H320
ethanol	CAS No 64-17-5	0.1 - < 1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Carc. 1A / H350 STOT SE 1 / H370 Flam. Liq. 2 / H225

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Hazardous ingredients, Consideration of other advice

*This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.*

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

- Handling of incompatible substances or mixtures

Do not mix with acids.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

Control of the effects

Protect against external exposure, such as

frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	2-butoxyethanol	111-76-2	REL	5 (10 h)	24 (10 h)						NIOSH REL
US	2-butoxyethanol	111-76-2	TLV®	20							ACGIH® 2019
US	2-butoxyethanol	111-76-2	PEL	50	240						29 CFR 1910.1000
US	2-butoxyethanol (EGBE) (glycol monobutyl ether)	111-76-2	PEL (CA)	20	97						Cal/OSHA PEL
US	potassium hydroxide	1310-58-3	REL						2		NIOSH REL
US	potassium hydroxide	1310-58-3	TLV®						2		ACGIH® 2019
US	potassium hydroxide (caustic potash)	1310-58-3	PEL (CA)						2		Cal/OSHA PEL
US	ethanol	64-17-5	TLV®			1,000					ACGIH® 2019
US	ethyl alcohol	64-17-5	REL	1,000 (10 h)	1,900 (10 h)						NIOSH REL
US	ethyl alcohol (ethanol)	64-17-5	PEL (CA)	1,000	1,900						Cal/OSHA PEL
US	ethyl alcohol (ethanol)	64-17-5	PEL	1,000	1,900						29 CFR 1910.1000

**Notation**

Ceiling-C  
STEL

ceiling value is a limit value above which exposure should not occur  
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	2-butoxyethanol	Butoxyacetic acid (BAA)	hydr, crea	BEI®	200 mg/g	ACGIH® 2019

Notation

crea creatinine  
hydr hydrolysis

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-butoxy-1-ethanol	111-76-2	DNEL	75 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
2-butoxy-1-ethanol	111-76-2	DNEL	98 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
potassium hydroxide	1310-58-3	DNEL	1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	80 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
ethanol	64-17-5	DNEL	1,900 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
ethanol	64-17-5	DNEL	343 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
ethanol	64-17-5	DNEL	950 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxy-1-ethanol	111-76-2	PNEC	8.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	0.88 mg/l	aquatic organisms	marine water	short-term (single instance)

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxy-1-ethanol	111-76-2	PNEC	463 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	35 mg/kg	benthic organisms	sediment	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	3.1 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	9.1 mg/l	aquatic organisms	water	intermittent release
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	0.69 mg/l	aquatic organisms	freshwater	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	1 mg/l	aquatic organisms	marine water	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	50 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	28 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	2.8 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	25 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethanol	64-17-5	PNEC	0.96 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethanol	64-17-5	PNEC	0.79 mg/l	aquatic organisms	marine water	short-term (single instance)
ethanol	64-17-5	PNEC	580 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethanol	64-17-5	PNEC	3.6 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethanol	64-17-5	PNEC	0.63 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethanol	64-17-5	PNEC	2.8 mg/l	aquatic organisms	water	intermittent release

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

##### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

**- Other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

**Environmental exposure controls**

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

**Appearance**

Physical state	liquid
Color	transparent - greenish yellow
Particle	not relevant (liquid)
Odor	characteristic

**Other safety parameters**

pH (value)	>14 (25 °C) (base)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 1,013 hPa closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	32 hPa at 25 °C
Density	1.1 g/ml
Vapor density	this information is not available
Relative density	1.1 (water = 1)
Solubility(ies)	not determined

**Partition coefficient**

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------



## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Auto-ignition temperature	230 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215° C)

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

#### 10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
2-butoxy-1-ethanol	111-76-2	oral	1,746 mg/kg
2-butoxy-1-ethanol	111-76-2	inhalation: vapor	11 mg/l/4h
potassium hydroxide	1310-58-3	oral	333 mg/kg
sodium dodecylbenzenesulfonate	25155-30-0	oral	650 mg/kg
ethanol	64-17-5	dermal	300 mg/kg

### Skin corrosion/irritation

Causes severe skin burns and eye damage.

### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
2-butoxy-1-ethanol	111-76-2	3	
ethanol	64-17-5	1	

### Legend

- 1 Carcinogenic to humans
- 3 Not classifiable as to carcinogenicity in humans

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### SECTION 12: Ecological information

#### 12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butoxy-1-ethanol	111-76-2	LC50	1,474 mg/l	fish	96 h
2-butoxy-1-ethanol	111-76-2	EC50	1,550 mg/l	aquatic invertebrates	48 h
2-butoxy-1-ethanol	111-76-2	ErC50	1,840 mg/l	algae	72 h
sodium dodecylbenzenesulfonate	25155-30-0	LC50	7.2 mg/l	fish	96 h
sodium dodecylbenzenesulfonate	25155-30-0	EC50	6.3 mg/l	aquatic invertebrates	48 h
ethanol	64-17-5	LC50	14 g/l	fish	96 h
ethanol	64-17-5	EC50	13 g/l	fish	96 h

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

None of the ingredients are listed.

#### 12.7 Other adverse effects

Data are not available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### SECTION 14: Transport information

<b>14.1 UN number</b>	
DOT	UN 1814
IMDG-Code	UN 1814
ICAO-TI	UN 1814
<b>14.2 UN proper shipping name</b>	
DOT	Potassium hydroxide solutions
IMDG-Code	POTASSIUM HYDROXIDE SOLUTION
ICAO-TI	Potassium hydroxide solution
<b>14.3 Transport hazard class(es)</b>	
DOT	8
IMDG-Code	8
ICAO-TI	8
<b>14.4 Packing group</b>	
DOT	III
IMDG-Code	III
ICAO-TI	III
<b>14.5 Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	
There is no additional information.	
<b>14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	
The cargo is not intended to be carried in bulk.	

#### Information for each of the UN Model Regulations

##### **Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Particulars in the shipper's declaration	UN1814, Potassium hydroxide solutions, 8, III
Reportable quantity (RQ)	27,051 lbs (12,281 kg) (potassium hydroxide) (1,4-dioxane)
Danger label(s)	8



Special provisions (SP)	IB3, T4, TP1
ERG No	154

##### **International Maritime Dangerous Goods Code (IMDG) - Additional information**

Marine pollutant	-
Danger label(s)	8



Special provisions (SP)	223
-------------------------	-----

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A
Segregation group	18 - Alkalis

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 8



Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** all ingredients are listed

#### Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

#### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
potassium hydroxide	1310-58-3		1	1000 (454)
sodium dodecylbenzenesulfonate	25155-30-0		1	1000 (454)

#### Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

#### Clean Air Act

none of the ingredients are listed

#### Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
2-butoxy-1-ethanol		1022			1.0 %
potassium hydroxide	1310-58-3				1.0 %
sodium dodecylbenzenesulfonate	25155-30-0				1.0 %

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### - Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
2-butoxy-1-ethanol	2-Butoxyethanol(EGBE)	111-76-2	A, O	skin
potassium hydroxide	Potassium hydroxide	1310-58-3	A	

#### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

### - Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
2-butoxy-1-ethanol	2-butoxyethanol (butyl cellosolve)	111-76-2		CA F2
potassium hydroxide	potassium hydroxide (caustic potash)	1310-58-3		CO R1
sodium dodecylbenzenesulfonate	SODIUM DODECYLBENZENE SULFONATE (BENZENESULFONIC ACID, DODECYL-, SODIUM SALT)	25155-30-0		
ethanol	ethyl alcohol (ethanol)	64-17-5		CA MU TE F3

#### Legend

- CA Carcinogenic
- CO Corrosive
- F2 Flammable - Second Degree
- F3 Flammable - Third Degree
- MU Mutagenic
- R1 Reactive - First Degree
- TE Teratogenic

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
ETHANOL, 2-BUTOXY-	111-76-2	
POTASSIUM HYDROXIDE (K(OH))	1310-58-3	E
BENZENESULFONIC ACID, DODECYL-, SODIUM SALT	25155-30-0	E

#### Legend

- E Environmental hazard

### - Hazardous Substance List (RI-RTK)

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Name of substance	CAS No	References
2-butoxy-1-ethanol	111-76-2	T
potassium hydroxide	1310-58-3	T, F
ethanol	64-17-5	T, F

**Legend**

F Flammability (NFPA®)  
T Toxicity (ACGIH®)

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
ethanol	ethanol (ethyl alcohol)	64-17-5	0.83	in alcoholic beverages	developmental

### VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 8.7 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 8.7 %

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

### National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
US	TSCA	all ingredients are listed
EU	REACH Reg.	all ingredients are listed

#### Legend

DSL Domestic Substances List (DSL)  
 REACH Reg. REACH registered substances  
 TSCA Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: <a href="http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement">http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement</a>
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	= EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control



## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

Abbr.	Descriptions of used abbreviations
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

## Blair Scrub Free Alkaline Tire & Wheel

Version number: GHS 1.0

Date of compilation: 2021-06-23

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H227	Combustible liquid.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H350	May cause cancer.
H370	Causes damage to organs.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.