

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

SECTION 1: Identification

1.1 Product identifier

Trade name

Impact

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Vehicle wash detergent

Uses advised against

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

1.3 Details of the supplier of the safety data sheet

Blair Enterprises LLC
18540 Apache Drive
Parker, CO 80138
1-720-383-4558

<https://blairceramics.com>
orders@blairceramics.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	1	Skin Corr. 1	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.6	carcinogenicity	2	Carc. 2	H351
B.16	substance or mixture corrosive to metals	1	Met. Corr. 1	H290

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05, GHS08



- Hazard statements

H290

May be corrosive to metals.

H314

Causes severe skin burns and eye damage.

H351

Suspected of causing cancer.

Impact

Version number: GHS 2.0

Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

- Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P234	Keep only in original container.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

trisodium nitrilotriacetate, anhydrous, potassium hydroxide, sodium hydroxide, sodium metasilicate, anhydrous

2.3 Other hazards

Hazards not otherwise classified

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
trisodium nitrilotriacetate, anhydrous	CAS No 5064-31-3	3 - < 12	Acute Tox. 4 / H302 Eye Irrit. 2 / H319 Carc. 2 / H351
disodium cocoamphodipropionate	CAS No 68604-71-7	3 - < 12	Eye Dam. 1 / H318 Flam. Liq. 4 / H227
sodium metasilicate, anhydrous	CAS No 6834-92-0	1 - < 3	Acute Tox. 4 / H302 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335
potassium hydroxide	CAS No 1310-58-3	1 - < 3	Acute Tox. 4 / H302 Skin Corr. 1A / H314 Met. Corr. 1 / H290
sodium hydroxide	CAS No 1310-73-2	1 - < 3	Skin Corr. 1A / H314 Eye Dam. 1 / H318 Met. Corr. 1 / H290

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Name of substance	Identifier	Wt%	Classification acc. to GHS
methanol	CAS No 67-56-1	0.1 - < 1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370 Flam. Liq. 2 / H225

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

- Handling of incompatible substances or mixtures

Do not mix with acids.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Control of the effects

Protect against external exposure, such as
frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	potassium hydroxide	1310-58-3	REL						2		NIOSH REL
US	potassium hydroxide	1310-58-3	TLV®						2		ACGIH® 2019
US	potassium hydroxide (caustic potash)	1310-58-3	PEL (CA)						2		Cal/OSHA PEL
US	sodium hydroxide	1310-73-2	REL						2		NIOSH REL
US	sodium hydroxide	1310-73-2	TLV®						2		ACGIH® 2019
US	sodium hydroxide	1310-73-2	PEL		2						29 CFR 1910.1000
US	sodium hydroxide (caustic soda)	1310-73-2	PEL (CA)						2		Cal/OSHA PEL
US	methanol	67-56-1	TLV®	200		250				H	ACGIH® 2019
US	methyl alcohol	67-56-1	REL	200 (10 h)	260 (10 h)	250	325				NIOSH REL
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.1000
US	methyl alcohol (methanol)	67-56-1	PEL (CA)	200	260	250	325	1,000			Cal/OSHA PEL

Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Notation

H	absorbed through the skin
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	methanol	methanol		BEI®	15 mg/l	ACGIH® 2019

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
trisodium nitrilotriacetate, anhydrous	5064-31-3	DNEL	9.6 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
trisodium nitrilotriacetate, anhydrous	5064-31-3	DNEL	3.2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
sodium metasilicate, anhydrous	6834-92-0	DNEL	6.2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
sodium metasilicate, anhydrous	6834-92-0	DNEL	1.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
potassium hydroxide	1310-58-3	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
sodium hydroxide	1310-73-2	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	270 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	0.93 mg/l	aquatic organisms	freshwater	short-term (single instance)
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	0.093 mg/l	aquatic organisms	marine water	short-term (single instance)
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	270 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	0.8 mg/l	aquatic organisms	water	intermittent release
methanol	67-56-1	PNEC	100 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	benthic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 mg/kg	pelagic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	1,540 mg/l	aquatic organisms	water	intermittent release
methanol	67-56-1	PNEC	21 mg/l	aquatic organisms	freshwater	short-term (single instance)
methanol	67-56-1	PNEC	2.1 mg/l	aquatic organisms	marine water	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	13 – 14 (25 °C) (base)
Melting point/freezing point	not determined
Initial boiling point and boiling range	90 °C
Flash point	>100 °C at 101 kPa closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	32 hPa at 25 °C
Density	1.1 g/cm ³ at 25 °C
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Temperature class (USA, acc. to NEC 500)

T3 (maximum permissible surface temperature on the equipment:
200°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
trisodium nitrilotriacetate, anhydrous	5064-31-3	oral	1,740 mg/kg
sodium metasilicate, anhydrous	6834-92-0	oral	1,349 mg/kg
sodium metasilicate, anhydrous	6834-92-0	inhalation: vapor	>2.1 mg/l/4h
sodium metasilicate, anhydrous	6834-92-0	inhalation: dust/mist	0.5 mg/l/4h
potassium hydroxide	1310-58-3	oral	333 mg/kg
methanol	67-56-1	oral	100 mg/kg

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
trisodium nitrilotriacetate, anhydrous		2B	

Legend

2B Possibly carcinogenic to humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
trisodium nitrilotriacetate, anhydrous	5064-31-3	LC50	114 mg/l	fish	96 h
trisodium nitrilotriacetate, anhydrous	5064-31-3	EC50	98 mg/l	aquatic invertebrates	96 h
trisodium nitrilotriacetate, anhydrous	5064-31-3	ErC50	>92 mg/l	algae	72 h
disodium cocoamphodipropionate	68604-71-7	LC50	1 - 100 mg/l	fish	72 h
disodium cocoamphodipropionate	68604-71-7	EC50	0.55 - 48 mg/l	algae	72 h

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
disodium cocoamphodi-propionate	68604-71-7	EC50	6.5 mg/l	daphnia	48 h
sodium metasilicate, anhydrous	6834-92-0	LC50	310 mg/l	fish	96 h
sodium metasilicate, anhydrous	6834-92-0	EC50	1,700 mg/l	aquatic invertebrates	48 h
sodium hydroxide	1310-73-2	EC50	40 mg/l	aquatic invertebrates	48 h
methanol	67-56-1	LC50	15,400 mg/l	fish	96 h
methanol	67-56-1	EC50	12,700 mg/l	fish	96 h
methanol	67-56-1	ErC50	22,000 mg/l	algae	96 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sodium metasilicate, anhydrous	6834-92-0	EC50	>100 mg/l	microorganisms	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 3266
IMDG-Code	UN 3266
ICAO-TI	UN 3266

14.2 UN proper shipping name

DOT	Corrosive liquid, basic, inorganic, n.o.s.
IMDG-Code	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
ICAO-TI	Corrosive liquid, basic, inorganic, n.o.s.
Technical name (hazardous ingredients)	potassium hydroxide, methanol

14.3 Transport hazard class(es)

DOT	8
IMDG-Code	8
ICAO-TI	8

14.4 Packing group

DOT	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	disodium cocoamphodipropionate

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN3266, Corrosive liquid, basic, inorganic, n.o.s., (contains: potassium hydroxide, methanol), 8, II, environmentally hazardous
Reportable quantity (RQ)	40,440 lbs (18,360 kg) (sodium hydroxide) (potassium hydroxide)
Danger label(s)	8, fish and tree



Environmental hazards	yes (hazardous to the aquatic environment)
-----------------------	--

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Special provisions (SP) B2, IB2, T11, TP2, TP27
ERG No 154

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant YES (hazardous to the aquatic environment) (disodium cocoamphodipropionate)

Danger label(s) 8, fish and tree



Special provisions (SP) 274

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-A, S-B

Stowage category B

Segregation group 18 - Alkalis

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)

Danger label(s) 8



Special provisions (SP) A3

Excepted quantities (EQ) E2

Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
methanol	67-56-1		1986-12-31

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methanol	67-56-1		3 4	5000 (2270)
potassium hydroxide	1310-58-3		1	1000 (454)
sodium hydroxide	1310-73-2		1	1000 (454)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
methanol	67-56-1				1.0 %
potassium hydroxide	1310-58-3				1.0 %
sodium hydroxide	1310-73-2				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
potassium hydroxide	Potassium hydroxide	1310-58-3	A	
sodium hydroxide	Sodium hydroxide	1310-73-2	A, N, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
methanol	methyl alcohol (methanol) (methanol)	67-56-1		TE F3
potassium hydroxide	potassium hydroxide (caustic potash)	1310-58-3		CO R1
sodium hydroxide	sodium hydroxide (caustic soda)	1310-73-2		CO R1

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Legend

CO Corrosive
F3 Flammable - Third Degree
R1 Reactive - First Degree
TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
METHANOL	67-56-1	E
POTASSIUM HYDROXIDE (K(OH))	1310-58-3	E
SODIUM HYDROXIDE (NA(OH))	1310-73-2	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methanol	67-56-1	T, F
potassium hydroxide	1310-58-3	T, F
sodium hydroxide	1310-73-2	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
methanol	methanol	67-56-1	0.34		developmental

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 0.63 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 0.63 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1	Cleaning Product Right to Know Act Substance List (CA-RTK)		yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Abbr.	Descriptions of used abbreviations
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Impact

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-06-23

Code	Text
H225	Highly flammable liquid and vapor.
H227	Combustible liquid.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H370	Causes damage to organs.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.