

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

SECTION 1: Identification

1.1 Product identifier

Trade name **Alkaline Presoak 416**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses **Vehicle wash detergent**

1.3 Details of the supplier of the safety data sheet

Blair Enterprises LLC
18540 Apache Drive
Parker, CO 80138
1-720-383-4558

<https://blairceramics.com>
orders@blairceramics.com

1.4 Emergency telephone number

Emergency information service **USA 1.800.535.5053, INTL 1.352.323.3500**
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word **danger**

- Pictograms

GHS05



- Hazard statements

H227 **Combustible liquid.**
H315 **Causes skin irritation.**
H318 **Causes serious eye damage.**

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

- Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling Alcohols, C9-11 ethoxylated, sodium metasilicate, anhydrous

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

Toxic to aquatic life (GHS category 2: aquatic toxicity - acute).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
sodium dodecylbenzenesulfonate	CAS No 25155-30-0	3 - < 12	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2A / H319
2-butoxy-1-ethanol	CAS No 111-76-2	3 - < 12	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 4 / H227
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	3 - < 12	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Eye Dam. 1 / H318
trisodium nitrilotriacetate, anhydrous	CAS No 5064-31-3	3 - < 12	Acute Tox. 4 / H302 Eye Irrit. 2 / H319 Carc. 2 / H351
sodium xylene sulphonate	CAS No 1300-72-7	1 - < 3	Skin Irrit. 2 / H315 Eye Irrit. 2B / H320
sodium metasilicate, anhydrous	CAS No 6834-92-0	1 - < 3	Acute Tox. 4 / H302 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

- Handling of incompatible substances or mixtures

Do not mix with acids.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	triethanolamine	102-71-6	PEL (CA)		5						Cal/OSHA PEL
US	triethanolamine	102-71-6	TLV®		5						AC-GIH® 2019
US	2-butoxyethanol	111-76-2	REL	5 (10 h)	24 (10 h)						NIOSH REL
US	2-butoxyethanol	111-76-2	TLV®	20							AC-GIH® 2019
US	2-butoxyethanol	111-76-2	PEL	50	240						29 CFR 1910.1000
US	2-butoxyethanol (EGBE) (glycol monobutyl ether)	111-76-2	PEL (CA)	20	97						Cal/OSHA PEL

Notation

Ceiling-C

STEL

TWA

ceiling value is a limit value above which exposure should not occur

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Biological limit values

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	2-butoxyethanol	Butoxyacetic acid (BAA)	hydr, crea	BEI®	200 mg/g	ACGIH® 2019

Notation

crea creatinine
hydr hydrolysis

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	52 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
sodium dodecylbenzenesulfonate	25155-30-0	DNEL	80 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	2,080 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Alcohols, C9-11 ethoxylated	68439-46-3	DNEL	294 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2-butoxy-1-ethanol	111-76-2	DNEL	75 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
2-butoxy-1-ethanol	111-76-2	DNEL	98 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
trisodium nitrilotriacetate, anhydrous	5064-31-3	DNEL	9.6 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
trisodium nitrilotriacetate, anhydrous	5064-31-3	DNEL	3.2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
sodium metasilicate, anhydrous	6834-92-0	DNEL	6.2 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
sodium metasilicate, anhydrous	6834-92-0	DNEL	1.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	0.69 mg/l	aquatic organisms	freshwater	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	1 mg/l	aquatic organisms	marine water	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	50 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	28 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	2.8 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
sodium dodecylbenzenesulfonate	25155-30-0	PNEC	25 mg/kg	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.1 mg/l	aquatic organisms	marine water	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1.4 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	14 mg/kg	benthic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	14 mg/kg	pelagic organisms	sediment	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	1 mg/kg	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 ethoxylated	68439-46-3	PNEC	0.014 mg/l	aquatic organisms	water	intermittent release
2-butoxy-1-ethanol	111-76-2	PNEC	8.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	0.88 mg/l	aquatic organisms	marine water	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	463 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	35 mg/kg	benthic organisms	sediment	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	3.1 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	9.1 mg/l	aquatic organisms	water	intermittent release
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	270 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	0.93 mg/l	aquatic organisms	freshwater	short-term (single instance)
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	0.093 mg/l	aquatic organisms	marine water	short-term (single instance)

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	270 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
trisodium nitrilotriacetate, anhydrous	5064-31-3	PNEC	0.8 mg/l	aquatic organisms	water	intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	purple
Particle	not relevant (liquid)
Odor	characteristic

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Other safety parameters

pH (value)	13 – 14 (25 °C) (base)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	67 °C at 1,013 hPa closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	32 hPa at 25 °C
Density	1 g/ml
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200 °C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
sodium dodecylbenzenesulfonate	25155-30-0	oral	650 mg/kg
Alcohols, C9-11 ethoxylated	68439-46-3	oral	1,200 mg/kg
Alcohols, C9-11 ethoxylated	68439-46-3	dermal	2,000 mg/kg
2-butoxy-1-ethanol	111-76-2	oral	1,746 mg/kg
2-butoxy-1-ethanol	111-76-2	inhalation: vapor	11 mg/l/4h
trisodium nitrilotriacetate, anhydrous	5064-31-3	oral	1,740 mg/kg
sodium metasilicate, anhydrous	6834-92-0	oral	1,349 mg/kg
sodium metasilicate, anhydrous	6834-92-0	inhalation: vapor	>2.1 mg/l/4h
sodium metasilicate, anhydrous	6834-92-0	inhalation: dust/mist	0.5 mg/l/4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
2-butoxy-1-ethanol	111-76-2	3	
trisodium nitrilotriacetate, anhydrous		2B	

Legend

2B Possibly carcinogenic to humans
3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sodium dodecylbenzenesulfonate	25155-30-0	LC50	7.2 mg/l	fish	96 h
sodium dodecylbenzenesulfonate	25155-30-0	EC50	6.3 mg/l	aquatic invertebrates	48 h
Alcohols, C9-11 ethoxylated	68439-46-3	LC50	8.5 mg/l	fathead minnow	96 h
Alcohols, C9-11 ethoxylated	68439-46-3	EC50	5.3 mg/l	daphnia magna	48 h
Alcohols, C9-11 ethoxylated	68439-46-3	ErC50	1 – 10 mg/l	algae	96 h
2-butoxy-1-ethanol	111-76-2	LC50	1,474 mg/l	fish	96 h
2-butoxy-1-ethanol	111-76-2	EC50	1,550 mg/l	aquatic invertebrates	48 h

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-butoxy-1-ethanol	111-76-2	ErC50	1,840 mg/l	algae	72 h
trisodium nitrilotriacetate, anhydrous	5064-31-3	LC50	114 mg/l	fish	96 h
trisodium nitrilotriacetate, anhydrous	5064-31-3	EC50	98 mg/l	aquatic invertebrates	96 h
trisodium nitrilotriacetate, anhydrous	5064-31-3	ErC50	>92 mg/l	algae	72 h
sodium metasilicate, anhydrous	6834-92-0	LC50	310 mg/l	fish	96 h
sodium metasilicate, anhydrous	6834-92-0	EC50	1,700 mg/l	aquatic invertebrates	48 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

SECTION 14: Transport information

- 14.1 **UN number** not subject to transport regulations
- 14.2 **UN proper shipping name** not relevant
- 14.3 **Transport hazard class(es)** not assigned
- 14.4 **Packing group** not assigned
- 14.5 **Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 **Special precautions for user**
There is no additional information.
- 14.7 **Transport in bulk according to Annex II of MARPOL and the IBC Code**
The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sodium dodecylbenzenesulfonate	25155-30-0		1	1000 (454)

Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

Clean Air Act

none of the ingredients are listed

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Right to Know Hazardous Substance List

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
2-butoxy-1-ethanol		1022			1.0 %
sodium dodecylbenzenesulfonate	25155-30-0				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
2-butoxy-1-ethanol	2-Butoxyethanol(EGBE)	111-76-2	A, O	skin

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- skin If a potential for absorption from skin contact merits special consideration, the word "skin" follows the substance name.

- Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications
2-butoxy-1-ethanol	2-butoxyethanol (butyl cellosolve)	111-76-2		CA F2
sodium dodecylbenzenesulfonate	SODIUM DODECYLBENZENE SULFONATE (BENZENESULFONIC ACID, DODECYL-, SODIUM SALT)	25155-30-0		

Legend

- CA Carcinogenic
- F2 Flammable - Second Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
ETHANOL, 2-BUTOXY-	111-76-2	
BENZENESULFONIC ACID, DODECYL-, SODIUM SALT	25155-30-0	E

Legend

- E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
2-butoxy-1-ethanol	111-76-2	T

Legend

- T Toxicity (ACGIH®)

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
2,2'-iminodiethanol	diethanolamine	111-42-2	0.013		cancer

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 6.6 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 6.6 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Legend

REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.2	Uses advised against: Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.		yes
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.2	- Hazardous ingredients for labelling: alkyl (C10-16) benzenesulfonic acid, monoethanolamine, Alcohols, C9-11 ethoxylated	- Hazardous ingredients for labelling: Alcohols, C9-11 ethoxylated, sodium metasilicate, anhydrous	yes
2.3		Hazards not otherwise classified: change in the listing (table)	yes
3.2		Description of the mixture: change in the listing (table)	yes
5.2	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Substance or mixture corrosive to metals.	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.	yes
7.2	- Corrosive conditions: Store in corrosive resistant container with a resistant inner liner.		yes

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
7.2	- Packaging compatibilities: Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.		yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.1		Relevant DNELs of components of the mixture: change in the listing (table)	yes
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
9.1	Explosive limits		yes
9.1	Lower explosion limit (LEL): 5.5 vol%		yes
9.1	Upper explosion limit (UEL): 17 vol%		yes
9.1	Density: 1.1 g/cm ³ at 25 °C	Density: 1 g/ml	yes
10.1	Reactivity: Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition. Substance or mixture corrosive to metals.	Reactivity: Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.	yes
11.1	Acute toxicity: Shall not be classified as acutely toxic.GHS of the United Nations, annex 4: May be harmful if swallowed or if inhaled.	Acute toxicity: Shall not be classified as acutely toxic.GHS of the United Nations, annex 4: May be harmful if swallowed.	yes
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)	yes
11.1	Skin corrosion/irritation: Causes severe skin burns and eye damage.	Skin corrosion/irritation: Causes skin irritation.	yes
11.1	Specific target organ toxicity - single exposure: May cause respiratory irritation.	Specific target organ toxicity - single exposure: Shall not be classified as a specific target organ toxicant (single exposure).	yes
12.1	Toxicity: Harmful to aquatic life with long lasting effects.	Toxicity: Toxic to aquatic life.	yes
12.1		Aquatic toxicity (acute) of components of the mixture: change in the listing (table)	yes
13.1	Waste treatment of containers/packages: Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	Waste treatment of containers/packages: Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	yes
14.1	UN number	UN number: not subject to transport regulations	yes
14.1	DOT: UN 1760		yes

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.1	IMDG-Code: UN 1760		yes
14.1	ICAO-TI: UN 1760		yes
14.2	DOT: Corrosive liquid, n.o.s.		yes
14.2	IMDG-Code: CORROSIVE LIQUID, N.O.S.		yes
14.2	ICAO-TI: Corrosive liquid, n.o.s.		yes
14.3	DOT: 8		yes
14.3	IMDG-Code: 8		yes
14.3	ICAO-TI: 8		yes
14.4	DOT: II		yes
14.4	IMDG-Code: II		yes
14.4	ICAO-TI: II		yes
14.7	Particulars in the shipper's declaration: UN1760, Corrosive liquid, n.o.s., 8, II		yes
14.7	Reportable quantity (RQ): 113,636 lbs (51,591 kg) (sodium hydroxide)		yes
14.7	Danger label(s): 8		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): B2, IB2, T11, TP2, TP27		yes
14.7	ERG No: 154		yes
14.7	Marine pollutant: -		yes
14.7	Danger label(s): 8		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 274		yes
14.7	Excepted quantities (EQ): E2		yes

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	Limited quantities (LQ): 1 L		yes
14.7	EmS: F-A, S-B		yes
14.7	Stowage category: B		yes
14.7	Danger label(s): 8		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): A3		yes
14.7	Excepted quantities (EQ): E2		yes
14.7	Limited quantities (LQ): 0,5 L		yes
15.1	Specific Toxic Chemical Listings (EPCRA Section 313): none of the ingredients are listed		yes
14.2	UN proper shipping name	UN proper shipping name: not relevant	yes
14.3	Transport hazard class(es)	Transport hazard class(es): not assigned	yes
14.4	Packing group	Packing group: not assigned	yes
14.7	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information: Not subject to transport regulations.	yes
14.7	International Maritime Dangerous Goods Code (IMDG) - Additional information	International Maritime Dangerous Goods Code (IMDG) - Additional information: Not subject to IMDG.	yes
14.7	International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information	International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information: Not subject to ICAO-IATA.	yes
15.1		Toxic Substance Control Act (TSCA): all ingredients are listed	yes
15.1		List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4): change in the listing (table)	yes
15.1		Toxic or Hazardous Substance List (MA-TURA): change in the listing (table)	yes
15.1		Hazardous Substances List (MN-ERTK): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (Chapter 323) (PA-RTK): change in the listing (table)	yes

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1	California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987: none of the ingredients are listed	California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987	yes
15.1		Proposition 65 List of chemicals: change in the listing (table)	yes
15.1	Regulated Volatile Organic Compounds (VOC-EPA): 13 %	Regulated Volatile Organic Compounds (VOC-EPA): 6.6 %	yes
15.1	Regulated Volatile Organic Compounds (VOC-Cal ARB): 13 %	Regulated Volatile Organic Compounds (VOC-Cal ARB): 6.6 %	yes
15.1		National inventories: change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in chapter 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Abbr.	Descriptions of used abbreviations
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Alkaline Presoak 416

Version number: GHS 2.0
Replaces version of: 2021-06-23 (GHS 1)

Revision: 2021-09-29

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H227	Combustible liquid.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.